



Optileb HY

Food grade hydraulic oils

Description

Optileb HY™ are food grade hydraulic oils with NSF-H1 approval, especially developed to meet the special requirements of the food and beverage industries. They are based on synthetic oils and contain carefully selected additives to prevent wear, oxidation and corrosion.

Optileb HY hydraulic oils comply with and even exceed DIN 51524 part 2 for HLP hydraulic oils.

Application

- For the special applications in the food and beverage industries where there may be exposure of the lubricated part to the edible product or its packaging
- For hydraulic systems in production, filling and packaging machines

Advantages

- OPTITEC® - OPTIMOL technology
- Physiologically safe, NSF H1 registration
- Tasteless and odorless
- No foam formation
- Excellent viscosity/temperature behavior
- Good water separation ability
- Miscible with mineral oil
- Disposal like mineral oil

Typical Characteristics

Name	Method	Units	HY 15	HY 32	HY 46	HY 68
ISO Viscosity Grade			15	32	46	68
Appearance	-	Visual	Transparent / Clear	Transparent / Clear	Transparent / Clear	Transparent / Clear
Base Oil	-	-	Polyalphaolefin	Polyalphaolefin	Polyalphaolefin	Polyalphaolefin
Density at +15°C/+59°F	g/ml	ISO 12185/ ASTM D4052/ DIN 51757	0.84	0.83	0.83	0.84
Kin. Viscosity at +40°C/+104°F	mm²/s	ISO 3104/ ASTM D445/ DIN 51562	15	30.5	43.6	65.6
Kin. Viscosity at +100°C/+212°F	mm²/s	ISO 3104/ ASTM D445/ DIN 51562	3.6	5.81	7.43	10.28
Viscosity Index	-	ISO 2909/ ASTM 2270/ DIN ISO 2909	125	136	136	143
Pour Point	°C/°F	ISO 3016/ ASTM D97/ DIN ISO 3016	< -50/ < -58	< -50/ < -58	-48/-54.4	-45/-49
Flash point	°C/°F	ISO 2592/ ASTM D92/ DIN ISO 2592	>200 / >392	219/426.2	242/467.6	242/467.6
Rust Test (24 hrs Synthetic sea water)	-	ISO 7210/ ASTM D665B/ DIN 51585	Pass	Pass	Pass	Pass
HY 15 23 Feb 2014 Castrol (A/C 390) logo and related marks are trademarks of Castrol Limited, used under licence.	HY 15 23 Feb 2014 Castrol (A/C 390) logo and related marks are trademarks of Castrol Limited, used under licence.	DIN 51354	12	12	>12	>12

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage to user's manufacturing plant or other material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol Industrial, Technology Centre , Whitchurch Hill , Pangbourne , Reading , RG8 7QR , United Kingdom

www.castrol.com/industrial